



5.1 CIPP Pipeline Inspection and QA/QC Best Practises

Training Module 6 for Andrews.engineer



CIPP Pipeline Rehabilitation Systems

Presented by:

Ian Ramsay

IRR Trenchless Consultancy & UKSTT Past Chairman and Andrews.engineer

2017-10-25



CIPP Pipeline QA/QC and Best Practises

Day	09.00		12.00		12.45	16.00	
1	5.1 Course Introduction	5.2 CIPP Rehabilitation Systems		L U N C H	5.3 CIPP Design and Specifications	5.4 CIPP Impregnation and Curing	
2	5.5 CIPP Systems Site and field issues, QA/QC, Defect analysis	5.10 Course Summary, Review					

CIPP Pipeline Rehabilitation Systems

We would like to thank the following persons and companies for the information and data provided in the preparation for this module (alphabetical order):

Dr. Dec Downey

ER Technical Services

Ka-Te

PMP

ProKASRO

Reline Europe

Sekisui

Thames Water

UKSTT

NASTT

Mark Pearson

Glossary of Terms O&M

Inspection: the routine or planned checking by visual means or by closed circuit television (CCTV) to ensure that the sewer, maintenance hole or other structure is performing satisfactorily.

Maintain: to keep the sewerage system operating in accordance with legal requirements.

Cleanse: clearance of chokes and blockages, including flushing when necessary.

Empty: provision and maintenance of a proper outfall and ensuring flow to that outfall.

Glossary of Terms: Sewer Rehabilitation

Rehabilitation: all aspects of upgrading the performance of existing sewer systems; structural rehabilitation includes repair, renovation and renewal.

Repair: rectification of damage or defect to the structural fabric of the sewer or installation and reconstruction of short lengths but not the reconstruction of the whole.

Renovation: methods by which the performance of a length of sewer is improved by incorporating the original sewer fabric but excluding isolated local repairs and root or silt removal.

Renewal: construction of a new sewer on, or off, the line of an existing sewer; the basic function and capacity of the new sewer being similar to those of the old.

Replacement: construction of a new sewer on, or off, the line of an existing sewer; the function of the new sewer will incorporate that of the old but may also include improvement and development work.

Glossary of Terms: Sewer Structural Grading

Sewer Grade: sewers are designated five different grades — 1, 2, 3, 4 and 5, depending upon their structural condition.

Grade 1 Sewer: acceptable structural condition

Grade 2 Sewer: minimal risk of collapse

Grade 3 Sewer: collapse unlikely in the near future but further deterioration likely

Grade 4 Sewer: collapse likely in the foreseeable future

Grade 5 Sewer: collapsed or collapse imminent

Clayware and Concrete Pipe Sewers

Internal Condition Grade	Typical Defect Descriptions
5	Already collapsed Deformation >10% and broken Extensive areas of fabric missing Fracture with deformation >10%
4	Broken Deformation up to 10% and broken Fracture with deformation 5-10% Multiple fracture Serious loss of level Spalling large Wear large
3	Fracture with deformation <5% Longitudinal cracking or multiple cracking Minor loss of level More severe joint defects, i.e. open joint (large) or joint displaced (large) Spalling medium Wear medium
2	Circumferential crack Moderate joint defects, i.e. open joint (medium) or joint displaced (medium) Spalling slight Wear slight
1	No structural defects

Brick Sewers (not exceeding 3 ring)

Internal Condition Grade	Typical Defect Descriptions
5	<ul style="list-style-type: none"> Already collapsed Missing invert Deformation >10% and fractured Displaced/hanging brickwork and deformation <10% Extensive areas of missing brickwork
4	<ul style="list-style-type: none"> Total mortar loss with deformation >10% Deformation up to 10% and fractured Displaced/hanging brickwork Small number of missing bricks Dropped invert Moderate loss of level Spalling large Wear large
3	<ul style="list-style-type: none"> Total mortar loss without other defects Single bricks displaced Deformation <5%, no fracture and only moderate mortar loss Spalling medium Wear medium
2	<ul style="list-style-type: none"> Minor cracking Surface mortar loss Spalling slight Wear slight
1	No structural defects

Localised Repair and Robotics

- CIPP Patch lining
- Resin Injection
- Re-rounding
- Joint Sealing
- Robotic systems
- Vacuum Excavation

Renovation Techniques and Materials

Non Man-entry Lining Techniques

Cured-in-Place Pipe

Lining with close fit pipe

Stabilisation (chemical grouting)

Non man entry in-situ coatings

Spiral Wound Lining

Sliplining

Renovation Techniques and Materials

Man-entry Lining Techniques

Man-entry lining with Pipe Segments and Panels

Lining with Discrete Pipes

Man-entry Insitu Coatings

CIPP Relining of Large Dia & Ovoid Sewers

Spiral Wound Lining

Cured in Place Best Practices

- **A client representative visiting projects**
- **Communicating with the Client and Contractor**
- **Recommends final acceptance**
- **Checks the QA/QC procedures**
- **Project Schedule**
- **Documentation review, (suppliers, contractor)**
- **Communication**

Cured in Place Best Practices

- Regular meeting attendance, facilitating communication between client and contractor
- Understand the procedure, equipment, materials being used
- Understands the schedule, specifications, requirements
- Technical data sheets, MSDS
- Safety requirements, Traffic management, highway or rail working
- Night schedule
- Checks and communicates that the project on track
- If testing required, co-ordinates with contractor
- If there are defects, causes and effect

Summary

- Understand
- Communicate
- Report

